

# **DMK 27AUJ003 Monochrome Camera**

The Imaging Source "27" Series USB 3.0 Camera



**Only 36×36×25 mm** 

Lens not included

The Imaging Source DMK 27AUJ003 monochrome camera has a USB 3.0 interface and is the perfect solution for many industrial automation, quality assurance, security, surveillance and medical applications.

The monochrome camera ships with the very sensitive 1/2.3 inch Aptina CMOS MT9J003 sensor. With up to 7 images per second, the DMK 27AUJ003 is a low cost, yet highly versatile imaging solution. The camera includes a C to CS mount adapter, making it compatible to C and CS mount lenses. Using the optional CS to M12 board lens adapter, the camera is also compatible to M12 board lenses.

The Imaging Source authors and supports drivers, SDKs, extensions and end-user software for Microsoft Windows, which can be freely downloaded from our web site. Extensions for Microsoft Windows enable the DMK 27AUJ003 to be integrated in to common machine vision software libraries, such as LabView and OpenCV. Furthermore, we author and support open source Linux drivers and software (Apache License 2.0) to integrate the camera into popular distributions. Download the Linux source code at GitHub.

#### **Features**

- USB 3.0 interface
- 1/2.3 inch Aptina CMOS sensor (MT9J003)
- 3,856×2,764 (10.7 MP)
- Up to 7 images per second
- Rolling shutter
- Only 36×36×25 mm
- Compatible to C and CS mount lenses
- Manufactured by The Imaging Source
- Ships with Windows and Linux software

#### **Accessories**

- CS to C mount adapter (shipped as standard)
- C and CS mount lenses
- CS to M12 board lens adapters
- M12 board lenses
- Standard USB 3.0 cable in various lengths
- 3 m USB 3.0 cable with fixing screws

#### **Device Drivers for Microsoft Windows**

Device Driver for USB Cameras

### Software Development Kits (SDKs) for Microsoft Windows

IC Imaging Control .NET Component for C#, VB.NET, C++ Class Library for C++ projects, IC Imaging Control C Library, IC 3D SDK - C, C++ library for stereo depth estimation, IC Imaging Control ActiveX, IC Imaging Control ActiveX Runtime Setup

#### **Extensions for Microsoft Windows**

TWAIN Source for IC Imaging Control, Cognex VisionPro AIK Plugin for IC Imaging Control, LabVIEW Extension for IC Imaging Control, IC Matlab Plugin for Matlab 10.0 R2010, IC Matlab Plugin for Matlab R2013b and higher versions, IC NeuroCheck Driver for NeuroCheck 6.0, IC NeuroCheck Driver for NeuroCheck 6.1

#### **End User Software for Microsoft Windows**

IC Capture - image acquisition, IC Measure - manual on-screen image measurement and image acquisition, IC 3D - User friendly stereo calibration, depth estimation and 3D visualization, IC Fullscreen Presenter, IC Line Profiler, Footswitch software for IC Capture, Scan2Docx, Scan2Docx, Scan2Docx, Scan2Docx OCR, Scan2Voice



# **DMK 27AUJ003 Specification**

### **GENERAL BEHAVIOR**

Dynamic range 8/12 bit

Video formats @ frame rate 3,856×2,764 (10.7 MP) Y800 @ 7 fps (maximum) 3,856×2,764 (10.7 MP) Y16 @ 4 fps

## INTERFACE (OPTICAL)

IR cut filter \*

Sensor type CMOS

Sensor specification On Semiconductor MT9J003

Shutter rolling

Format <sup>1</sup>/<sub>2.3</sub> inch

Pixel size H: 1.67 μm, V: 1.67 μm

Lens mount C/CS

## INTERFACE (ELECTRICAL)

Interface USB 3.0

Supply voltage 4.5 VDC to 5.5 VDC

Current consumption approx 250 mA @ 5 VDC

Auto iris control

Trigger \*

I/Os 🗶

### **INTERFACE (MECHANICAL)**

Dimensions H: 36 mm, W: 36 mm, L: 25 mm

Mass 70 g

### **ADJUSTMENTS**

Shutter  $^{1/}_{20,000}$  s to  $^{1/}_{4}$  s

Gain 0 dB to 12 dB

# **ENVIRONMENTAL**

Temperature (operating) -5 °C to 45 °C Temperature (storage) -20 °C to 60 °C

Humidity (operating) 20 % to 80 % (non-condensing)


Humidity (storage) 20 % to 95 % (non-condensing)

Subject to change




# **Aptina MT9J003 Spectral Response Curve**


CMOS Sensor in DMK 27AUJ003





# **DMK 27AUJ003 Dimensional Diagram**







# Machine vision, designed in Germany



Ever since The Imaging Source was founded in 1990, it has been one of the leading manufacturers of industrial cameras, frame grabbers and video converters for automation, quality assurance, logistics, medicine, science and security.

Our extensive range of industrial cameras ships with USB 3.0, USB 2.0, GigE, FireWire 800 and FireWire 400 interfaces. Thanks to their multi-purpose features and extremely high quality standards, the cameras are commonly used in demanding applications.

The software support offered by the cameras fulfill the requirements of demanding end-users and programmers. The cameras can be put into operation within a few minutes, or integrated into new or existing applications with only a few lines of code. All camera drivers are Microsoft certified. The easy of which the cameras can be integrated, the corresponding low integration costs, and the high quality of the software set the industry standard.

All cameras, frame grabbers and video converters, manufactured by The Imaging Source, are the result of decades of experience, uncompromisingly high quality standards, and continual development. Developers and system engineers prefer The Imaging Source cameras due to their ease of system integration.



# **World-Class Software and Customer Care**



What really separates The Imaging Source from its competitors is the comprehensive Windows and Linux software available free of charge with all its products, and the unsurpassed level of customer service.

The Imaging Source authors and supports device drivers, software development kits (SDKs), programming samples, extensions, end-user software and software tools for Microsoft Windows. All Windows software can be download directly from our web site:

## http://www.theimagingsource.com


Additionally, The Imaging Source authors and supports open source drivers and end-user software for Linux. The Linux source code, which is released under the Apache License 2.0, enables you to integrate all machine vision cameras into popular Linux distributions. The Open Source code is available to download from GitHub:

# https://github.com

The Imaging Source guarantees fast and efficient customer service for all hardware and software issues via our skilled customer service representatives. Not only will we provide support regarding technical issues, but we will also work with you to implement our components into your project. Contact customer service at:

http://www.theimagingsource.com





## PRESENT ALL OVER THE WORLD

# THE IMAGING SOURCE, LLC

Suite 400 6926 Shannon Willow Rd Charlotte, NC 28226 United States

Tel: +1 704-370-0110 Fax: +1 704-542-0936

# THE IMAGING SOURCE EUROPE GMBH

Überseetor 18 28217 Bremen Germany

Tel: +49 421 335910 Fax: +49 421 3359180

# THE IMAGING SOURCE ASIA CO., LTD.

2F., No.8, Xinhu 1st Road Taipei City 114, Neihu District Taiwan

Tel: +886 2 2792 3153 Fax: +886 2 2792 6583

All product and company names in this document may be trademarks and tradenames of their respective owners and are hereby acknowledged. The Imaging Source, LLC cannot and does not take any responsibility or liability for any information contained in this document. The source code in this document may be used exclusively used for educational purposes. The Imaging Source, LLC does not assume any kind of warranty expressed or implied, resulting from the use of the content of this document or the source code. The Imaging Source, LLC reserves the right to make changes in specifications, function or design at any time and without prior notice.